

金方圆密封材料有限公司

XIXIA JINFANGYUAN SEALING MATERIALS CO.,LTD.



JFY-1240

JFY-1240 Graphite Packing Reinforced by Multi-Inconel Wire 镍基石墨盘根

DESCRIPTION 描述:

Made of graphite yarn reinforced by Inconel wire 1 to 5 inside; there are multi Inconel wires reinforcement to create the graphite packing with increased extrusion resistance and higher pressure capability.

采用茵苛镍丝增强石墨线编织而成。具有良好的热传导性，耐化学性及自润滑；每根石墨线内1~5根茵苛镍丝增强大大提高了盘根的机械强度。

APPLICATION 应用:

It retains all the inherent benefits of normal graphite packing. Low coefficient of friction and the multi Inconel wire reinforcement make it ideal for rotary shafts of pumps, agitators, mixers, crystallizers, filters, continuous digesters, reciprocating pump rods.

与普通柔性石墨盘根相比，镍基石墨盘根保留了普通柔性石墨盘根的全部优点。适用于大多数化学介质、酸、碱等，尤其适合于高温、高压的蒸汽中。

GENERAL PARAMETER 一般参数:

Technical data	Rotating旋转泵	Reciprocating往复泵	Valves阀门
Pressure压力	3 Mpa	10 Mpa	30 Mpa
Shaft speed线速度	23 m/s rotary		
Temperature温度	-200℃ to +455℃ Atmosphere常温; to +650℃ in Steam蒸汽下		
PH range PH值	0~14		

Types of other reinforced metal wire for graphite packing: 其他金属丝增强石墨盘根:

JFY-1230 Graphite Packing Reinforced by Multi- SS304 Wire 不锈钢丝增强石墨盘根

Made of graphite yarn reinforced by SS304 wire; compared with 1240, it has the similar performance, but more economical efficiency.
采用SS304不锈钢丝增强石墨线编织而成。性能与JFY-1240相似，具有更好的经济性。

JFY-1250 Graphite Packing Reinforced by Multi- Copper Wire 铜丝增强石墨盘根

It is made of graphite yarn reinforced by copper wire to further improve electricity conduct.
采用铜丝增强石墨线编织而成，进一步提高盘根的导电性。

PACKAGE 包装:

In coils of 5 kg, 10kg, 25kg, Packing Rings also available. Other packaging according to customer requirements Supply OEM products.
5公斤/卷，10公斤/卷，25公斤/卷。盘根填料环也可提供。其他包装按照客户要求。

