



**JFY-H2000**

### JFY-H2000 Graphite Ring 石墨环

#### DESCRIPTION& APPLICATION描述&应用:

JFY-H2000 is formed by molding flexible graphite tape or flexible graphite braided packing, metal materials can also be put in, they are often used together. Mainly used for sealing of valves, pumps and expansion joints which are used in oil industry, chemical industry, thermoelectric station, nuclear, etc.

JFY-H2000石墨填料环是由柔性石墨纸或者石墨盘根通过模具压制而成。

#### GENERAL PARAMETER 一般参数:

Temperature温度	-240~650
Pressure压力	30Mpa
Density密度	1.75~2.0g/cm <sup>3</sup>
PH range HP值	0~14
Size()尺寸	5~1500mm



**JFY-T140**

### JFY-T140 Corrugated graphite tape with adhesive coating 石墨波纹带

#### DESCRIPTION& APPLICATION描述&应用:

It cut from pure graphite roll by exact lathe, and then presses it with corrugated profile by special calendar. Designed for use as packing, just with wrapping tape to stem or shaft, and then stuffing, endless packing can be formed. It's easily installed for small diameter valves, and can also be used for emergencies when spare packing is not available.

该带由高精度车床把石墨卷材分切成带状，然后经专用的花纹压辊滚压成波纹状。在作为盘根填料函使用时，直接把石墨带缠绕在泵、阀的轴上，缠绕至一定尺寸后，用压盖压实即可。对于小直径阀门及其它应急维修中相当方便，大大节约工厂库存。

#### SERVICE LIMITS服务范围:

Temperature 温 度:	-240~500℃ under oxidizing environment
	-240~3500℃ under non-oxidizing environment
	-240~3500℃ ( 无氧环境 )
PH Range PH 值	0 - 14

