

金方圆密封材料有限公司

XIXIA JINFANGYUAN SEALING MATERIALS CO.,LTD.

JFY-4300A Expanded PTFE Joint sealant Tape with self-adhesive
膨体四氟带（带背胶）



JFY-4300A

DESCRIPTION& APPLICATION描述&应用:

JFY-4300A Expanded PTFE Joint sealant Tape with self-adhesive. The tape is very novel sealing material made of pure PTFE through a unique process, tensile strength. This product is an ideal sealing material applied at the positions of intermediate and low temperature. The filling is convenient and quick, it does not need to dismantle the valve, only need to circle the filling on the valve lever, thrusts it into the packing box, press the cap of the box, it will be pressed densely, also because its soft plastic deformation, it can fill the leakage gap automatically.

JFY4300A膨体四氟带，具有很好的柔韧性、压缩回弹性、耐蠕变性、耐高低温性及优异的耐腐蚀性、不老性、自润滑性。

用途:

- ▲各种搪瓷衬里、玻璃衬里、塑料衬里、橡胶衬里、石墨衬里及不锈钢、钛钢的 塔、热交换器、反应釜等法兰面的密封；
- ▲各种管道和管配件的法兰面密封；
- ▲表面加工精度较差，不平整区域较大，形状不规则，螺栓紧固力不易用足或不宜过大的大口径设备的法兰面密封；
- ▲强腐蚀介质和不能被丝毫污染的流体的密封。

SERVICE LIMITS服务范围

Mediator 介质	Acids, alkalis, solvents, gases most of the chemical mediator. 酸、碱、溶剂、气体大部分的化学介质
Pressure工作压力	10 Mpa
Density密度	A/B: 0.70/0.80g/cm ³
Temperature温度	-240 ~ 260℃
PH range PH值	0 - 14

STOCK DIMENSIONS常规尺寸

Width宽度(mm)	Thickness厚度 mm	Length长度 M/roll	Width宽度 mm	Thickness厚度 mm	Length长度 M/roll
1.5	3.0	30	15	5.0	5
3	2.0	30	16	3.0	5
5	2.0	20	16	5.0	5
6	3.0	15	17	5.0	5
7	2.5	15	18	5.0	5
8	3.0	15	20	5.0	5
9	4.0	10	25	5.0	5
10	3.0	10	30	5.0	5
10	4.0	10	40	4.0	5
12	4.0	8	50	3.0	5
14	5.0	5	100	1.0	5