

金方圆密封材料有限公司

XIXIA JINFANGYUAN SEALING MATERIALS CO.,LTD.

Expanded graphite sheet 石墨板材



DESCRIPTION 描述:

GCCSEAL pure expanded graphite sheets & rolls are selected from the high purity natural flake graphite. They are made through the advanced chemical treatment and mechanical procedure without fibers, binders or other additives. It offer excellent sealing capabilities under extreme conditions with a longer life and less maintenance

金方圆系列纯石墨板材由天然高纯鳞片石墨经化学及高温处理，模压或滚压而成，无任何粘接剂。在苛刻的工况条件下仍具有极好的密封性能，使用寿命长，维护费用低。

GCCSEAL-Style graphite sheets 石墨板材系列:

Style型号	Products	产品名称
JFY-1500	Expanded graphite sheet/roll	纯石墨板材(卷材)
JFY-1500P	Graphite sheet reinforced with smooth metal	平板增强石墨板材
JFY-1500T	Graphite sheet reinforced with tanged metal	齿板增强石墨板材
JFY-1500M	Graphite sheet reinforced with metal mesh	金属网增强石墨板材

DIMENSIONS 相关标准:

Style 型号	Composition 结构图示	Tmax最高温度: °C		Pmax 最大压力 Mpa	Compressibility 压缩率 ≥ %	Recover 回弹率 ≥ %	Gas permeability 气体渗透率 cm ³ /min ≤	Recover 回弹率 ≤
		SS304	SS316					
JFY-1500		450	560	4	30	15	0.4	0.4
JFY-1500P		450	560	5	35	15	0.4	0.5
JFY-1500T		450	560	5	40	18	0.8	0.5
JFY-1500M		450	560	5	40	15	1.0	58

SIZE尺寸:

1000 x 1000 x 1.0 ; 1.5 ; 2.0 ; 3.0mm 1500 x 1500 x 1.0 ; 1.5 ; 2.0 ; 3.0mm
 1000 x 2000 x 1.0 ; 1.5 ; 2.0 ; 3.0mm 1500 x 2000 x 1.0 ; 1.5 ; 2.0 ; 3.0mm

Cork Products 软木制品



JFY-CS Cork sheet is made of clean granulated cork mixed with resin binder, which is compressed to form block, then split into sheets. The sheets have properties of good resilience, good resistance to water, oil and solvents, and good compressibility and so on

JFY-CS软木板材由天然的洁净软木颗粒配以特殊的树脂，模压成软木块料，然后切割成各种厚度及尺寸的板材，软木制品具有许多优秀的性能，如：极好的压缩性，回弹性，能防水、油及一般的溶剂等，可用来制作各种密封垫板，软木塞、软木地板，甚至软木工艺品等。

sheet板材:

950 x 640mm x 0.8~100 mm
 915 x 610mm x 0.8~100 mm

Roll卷材:

1220mm x Length x 1~6 mm